


BM94100BL

100V, 15A⁽¹⁾, TBR series Schottky

Mechanical Data

Chip Drawing	Item	Information	
	Die Size (A)	2388 μm	94 mil
	Top Metal Pad Size (B)	2202 μm	86.7 mil
	Passivation Seal (C)	2308 μm	90.9 mil
	Wafer Thickness (D)	254±15 μm	10±0.6 mil
	Scribe Line Width (E)	80μm	3.15 mil
	Wafer Diameter	6 inch	
	Gross Die	2705	
	Top Side Metallization/ Layer Thickness	Al / 5 ±0.5 μm	
	Back Side Metallization/ Layer Thickness	Ag / 2 ±0.2 μm	
	Recommended Storage Environment	Store in original container, in dry nitrogen, (6 months at an ambient temperature of 23°C±3°C)	

Electrical Characteristics in C/P test (T_J=25°C)

Parameter	Description	Min.	Typ.	Max.	Unit	Test Condition
V _{BR}	Reverse Breakdown Voltage	100	—	—	V	I _R = 300μA
V _F	Instantaneous Forward Voltage	—	0.465	0.49	V	I _F = 3A ⁽²⁾
		—	0.63	0.67	V	I _F = 10A ⁽²⁾
I _R	Reverse Leakage Current	—	12	20	μA	V _R = 100V
T _J , T _{STG}	Operating and Storage Temperature	-40°C to 150°C Max				